

This Tech Sheet applies to the following Series:

METSW METSU METDU MMEX CMEXR

Energy Data Chart – Options

Standard fixture (AC)

	Normal Operation			
	Red LEDs		Green LEDs	
	120V	277V	120V	277V
Input Power (W)	2.08	2.18	2.42	2.52
Input Current	0.03	0.01	0.03	0.01
(A) Power Factor	0.60	0.62	0.64	0.64

EL Option

	Normal Operation				Charging			
	Red LEDs		Green LEDs		Red LEDs		Green LEDs	
	120V	277V	120V	277V	120V	277V	120V	277V
Input Power (W)	3.47	3.57	3.49	3.59	4.77	4.81	4.78	4.76
Input Current	0.04	0.02	0.04	0.02	0.05	0.02	0.05	0.02
(A) Power Factor	0.66	0.66	0.66	0.66	0.74	0.74	0.73	0.73

CEL Option

	Low Temp. Operation				Low Temp. Charging			
	Red LEDs		Green LEDs		Red LEDs		Green LEDs	
	120V	277V	120V	277V	120V	277V	120V	277V
Input Power (W)	8.20	8.46	8.21	8.63	9.50	9.70	9.50	9.80
Input Current (A)	0.09	0.04	0.09	0.04	0.10	0.04	0.10	0.04
Power Factor	0.76	0.76	0.76	0.78	0.82	0.83	0.82	0.82

XAC Option

	Normal Operation				Auxiliary Operation			
	Red LEDs		Green LEDs		Red LEDs		Green LEDs	
	120V	277V	120V	277V	120V	277V	120V	277V
Input Power (W)	2.46	2.50	2.50	2.53	2.86	2.91	2.91	2.95
Input Current (A)	0.03	0.01	0.03	0.01	0.03	0.02	0.03	0.02
Power Factor	0.66	0.66	0.67	0.67	0.70	0.70	0.71	0.70

XDC Option

	Normal Operation				Auxiliary Operation					
	Red LEDs		Green LEDs		Red LEDs			Green LEDs		
	120V	277V	120V	277V	6V	12V	24V	6V	12V	24V
Input Power (W)	2.48	2.49	2.44	2.49	0.90	1.80	3.10	0.95	1.98	3.09
Input Current (A)	0.03	0.01	0.03	0.01	0.15	0.15	0.13	0.16	0.15	0.13
Power Factor	0.67	0.68	0.67	0.66						



METSW



METSU



METDU



MMEX



CMEXR

